

# DATA SHEET

## CAL-EDGE-0 GATEWAY

2025 CALMS inc.



## **CAL-EDGE-0 gateway**

The CAL-EDGE-0 device is a highly sophisticated and affordable remote data logger for compressed air systems. Device connects directly to CALMS web application which provides real time access to data from any web browser for any end user and their service partner. It can be configured for majority of compressors and sensors on the market.

### **Key features and benefits**

- > Plug & Play device, easiest and cheapest solution used for remote monitoring and auditing, alarming and reporting, designed for compressed air systems;
- > CALMS provides detailed system analysis with auto-generated efficiency warnings, savings estimates based on best-in-class benchmarks, and high-resolution data logging (up to 1-second sampling);
- > Helps improve your energy efficiency and shows where to save on energy costs;
- > Ability to connect to almost any compressor and sensor;
- > Increases your environmental image;
- > Increases the reliability of your equipment;
- > Robust industrial design.

Specifications		
Description	CAL-EDGE-0	Remarks
Hardware	Quad core Cortex-A53 (ARM v7) 64-bit SoC @ 1.5GHz, 1GB DDR2 RAM	
Protocol	MODBUS RTU, MODBUS TCP/IP, OPC UA	Up to 20 sensor per one device
Interfaces	1x 10/100 Mbps Ethernet adapter	
Analog inputs 4...20mA	0	
RS485	Standard: 1x	2-wire RS485 (half duplex)
WEB management	Yes	
Min. logging interval	1 sec (configurable)	
Data Storage	eMMC 8 GB	
Cloud connection	Mobile 3G/4G / LAN	
Operating Range	-25 – 60 C (-13 F – 140 F)	
Power supply	24VDC	Recommended: <b>50W</b> . Power supply included
Cellular modem	LTE EG25-G Module	Depends on network coverage
Antenna interface	Standard SMA interface-antenna included	
Size	H 30 x W 110 x L 130 mm H 1.18 x W 4.33 x L 5.12 Inches	
Weight	511 g / 1,13 lb	
Materials	Enclosure: Aluminum	
Mounting	DIN rail or wall mounting	
EMC	EN 61000-6-2 EN 61000-6-3	
Approvals	CE / UL / FCC Class A	

## Product information and accessories

### Product:

### Description:

#### CAL-EDGE-0



CALMS-EDGE-0 survey device LTE 4G with Modbus RTU & TCP/IP;  
 Portable measurement device with Ethernet, RS485 and CAN interface connection  
 Supported protocols: Modbus RTU, TCP/IP, OPC UA (without sensors)  
 3G/4G Modem SMA with external antenna (with SIM card provided EU/Global);  
 1 x Ethernet port 10/100 Base-T (LAN);  
 1x RS485 port and 1x CAN port;  
 Internal memory eMMC 8GB, optional  $\mu$ SD 256 GB  
 Ambient temperature range: -25°C to +60°C  
 Power Supply included 24VDC, 2.1A, 50W;  
 Approval UL / CE / FCC Class A

### Accessories

### Description

#### CAL-ANTENNA-EXT

Antenna extension cable  
 Attenuation: 2.4 Ghz 0.55 dB per meter 5.7 Ghz 0.86 dB per meter  
 Diameter: 4.80 mm,  
 Cable length: approx. 10 m

#### CAL-CABINET

Steel cabinet for wall mounting, ready to install CAL-EDGE-0 and modules (not included)  
 Steel cabinet size: 380x380x210 with CALMS design  
 Power supply: 24VDC, 60W  
 Cable glands, terminals, circuit breaker, prewired

#### CAL-RS485-SHARER

3port RS-485 Port Sharer  
 Used to share MODBUS slave data with two MODBUS masters.

#### SENSORS

Measuring equipment is optional and available under Measurement

***Europe***

CALMS d.o.o.  
Dolenjska cesta 83  
1000 Ljubljana, SI  
E: [info@calms.eu](mailto:info@calms.eu)  
T: [+386-1-5632-063](tel:+386-1-5632-063)  
[www.calms.eu](http://www.calms.eu)

***USA***

CALMS AIR Inc.  
9457 S University Blvd #710  
Highlands Ranch, CO 80126, USA  
E: [info@calms.com](mailto:info@calms.com)  
T: [+1-720-299-1589](tel:+1-720-299-1589)  
[www.calms.com](http://www.calms.com)

***Nordic***

CALMS Nordic AB  
Linnégatan 30  
413 04 Göteborg, Sweden  
E: [info@calms.se](mailto:info@calms.se)  
T: [+46-31-757-15-15](tel:+46-31-757-15-15)  
[www.calms.se](http://www.calms.se)